

SRP-350

T H E R M A L R E C E I P T P R I N T E R

• Dimension



• D & P(Drop and Print) Paper Supply



• Back Side



- Serial Interface
- Drawer Port
- Power Jack

■ Fastest Printing Speed (150mm / sec, 47.2 LPS)

■ Multiple Interface (RS-232C, RS-485, USB, IEEE-1284) Modular Interface Card

■ Saves Installation Space (Compact Size, Wall-Mount)

■ Easy-to-use

- D & P (Drop and Print) paper supply
- Simple to eliminate Paper Jam
- Complete Compatibility


■ Specifications

		SRP-350
PRINT	Printing Method	Direct Thermal
	Printing Speed	150 mm/sec (47.2 LPS)
	Dot Density	180 dpi (7 dot/mm)
	Printing Direction	Unidirectional with friction feed
	Character per Line	Font A : 42 Font B : 56
PAPER SPECIFICATION	Paper Type	Thermal Paper
	Paper width	79.5 - 0.5 mm
	Paper Roll Diameter	Max. φ 83.0 mm
PAPER SUPPLY METHOD		D & P (Drop and Print) Mechanism
RELIABILITY	MCBF	37,000,000 Lines
	TPH Life	1 x 10 ⁸ pulse, 100 km
CHARACTER SET		Alphanumeric Character : 95
		Extended Graphic : 128 x 7 page (1 space page)
		International character : 32
BARCODE		EAN-13, EAN-8, CODE 39, CODE 93, CODE 128, ITF, CODE BAR, UPC-A, UPC-E
		TM-88 (II), TSP552 (II)
EMULATION DRIVER		DCS, Windows 3.1 / 95 / 98 / NT
SENSOR		Near end sensor, Paper end sensor
DRAWER PORT		2 port
INTERFACE		RS-232C (Standard)
OPTION I / F CARD		RS-232C, RS-485, USB, IEEE-1284
POWER SUPPLY		AC 120V ~ 230V - 10% (Adapter)
DIMENSION (W X L X H mm)		145 x 195 x 146
AUTO CUTTER	Type	Guillotine
	Life	1,000,000 cuts

■ Options

WM-350

Wall Mount Bracket



Chic White

Dark Gray



HEAD OFFICE & SALES DEPT.
 FactoryWorld 705, 332-2, Wonchon Dong,
 Paldal Gu, Suwon, Kyunggi Do, Korea, 442-822
 TEL : +82-31-218-5522 FAX : 82-31-218-5589
<http://www.samsungminiprinters.com>

Distributed by :

* Design & Specifications are subject to change without notice.
 2003. 02